



Cleantime CT40 Scrubber Drier

Specifications

Part No. Model	LPTB00399 CT40B50	LPTE00304 CT40C50	LPTB01096 CT40BT50
Power supply	24V	240v 50Hz	24V
Traction system	Brush	Brush	120W Fwd & Rev.
Scrub width	500 mm.	500 mm.	500 mm.
Squeegee width	815 mm.	815 mm.	815 mm.
Capacity; solution	40 lt.	40 lt.	40 lt.
Capacity; recovery	50 lt.	50 lt.	50 lt.
Brushes	1; disk	1; disk	1; disk
Brush motor	600W	1000W	600W
Vacuum motor	480W	550W	480W
Productivity	1750 m ² /hr	1750 m ² /hr	2250 m ² /hr
Sound level	67 dB(A)	67 dB(A)	67 dB(A)
Weight	127 kgs.	83 kgs	133 kgs.



Standard Equipment

- Nylon brush
- Pad driver
- Batteries (for 24V models)
- Charger (for 24V models)

Features

- Simple operator controls
- Easy to maneuver with water weight balanced over wheels
- Self Leveling System (SLS) allows the brush to adapt to irregular surfaces.
- Solenoid operated solution flow.
- Anti foam system to protect vacuum motor
- Oil bath reduction gearbox on brush motor
- Brush replacement without tools.
- Made in Italy

Service Parts

Squeegee blade front	MPVR51017
Squeegee blade rear	MPVR51018
Brush – nylon (std)	SPPV43963

Options

Bassina brush	SPPV45469
Tynex brush	SPPV44837

Recommended uses

- Contractors
- Hospitals
- Aged Care
- Shops