



Cleantime CT60 Scrubber Drier

Specifications

Part No. Model	LPTB00384 CT60B50	LPTB00388 CT60BT55	LPTB02012 CT60BT60	LPTB02013 CT60BT55R
Power supply	24V	24V	24V	24V
Traction system	Brush	120W Fwd.	120W Fwd.	120W Fwd.
Scrub width	500 mm.	540 mm.	600 mm.	550 mm.
Squeegee width	815 mm.	815 mm.	815 mm.	815 mm.
Capacity; solution	60 lt.	60 lt.	60 lt.	60 lt.
Capacity; recovery	70 lt.	70 lt.	70 lt.	70 lt.
Brushes	1; disk	1; disk	2; disk	2; roller
Brush motor	600W	600W	600W	600W
Vacuum motor	480W	480W	480W	480W
Productivity	1750 m ² /hr	1850 m ² /hr	2250 m ² /hr	2100 m ² /hr
Sound level	64 dB(A)	64 dB(A)	67 dB(A)	70 dB(A)
Weight	123 kgs.	123 kgs.	155 kgs.	154 kgs.



Standard Equipment

- Batteries
- Charger
- Brush/es
- Pad driver/s (Not on roller model)
- 6 lt. hopper on roller model

Features

- Simple operator controls
- Easy to maneuver with water weight balanced over wheels
- Self Leveling System (SLS) allows the brush to adapt to irregular surfaces.
- Solenoid operated solution flow.
- Anti foam system to protect vacuum motor
- Brush replacement without tools (disc models).
- Made in Italy

Service Parts

Squeegee blade front		MPVR45195
Squeegee blade rear		MPVR45194
Brush – nylon (std)	50cm	SPPV43963
	55cm	SPPV43964
	60cm	SPPV45721
	55R	SPPV00343

Options

Bassina brush	50 cm	SPPV45469
	55cm	SPPV45732
	60cm	SPPV45722
	55R	SPPV00344
Tynex brush	50cm	SPPV44837
	55cm	SPPV45733
	60cm	SPPV45723
	55R	SPPV00345

Recommended uses

- Contractors
- Hospitals
- Aged Care
- Shops
- Factories (roller model)
- Warehouses (roller model)